

## Technical Information

No. 4202

Edition: 08/05 - subject to change

Substitutes: Edition 06/01

Status: valid

Xenon Short Arc Lamp

# XBO<sup>®</sup> 4200 W/CA OFR

### ■ Product description

The OSRAM XBO<sup>®</sup> 4200 W/CA OFR is a DC-operated lamp that is especially suited for applications requiring excellent arc stability and high luminance. The OSRAM XBO<sup>®</sup> 4200 W/CA OFR is designed for vertical burning position (CA = cable on anode base).

### ■ Technical data

Order reference	XBO <sup>®</sup> 4200 W/CA OFR	
Rated lamp wattage	W	4200
Rated lamp voltage	V	29
Rated lamp current (=)	A	140
Current control range	A	80/160
Ignition voltage	kV <sub>P</sub>	33
Min. open circuit voltage for cold / hot ignition	V	75/100
Luminous flux	lm	190000
Luminous intensity	cd	20000
Average luminance	cd/cm <sup>2</sup>	100000
Luminous area w x h *)	mm	2.1 x 5.7
Electrode gap e (cold)	mm	7.0
Lamp length (overall) l <sub>1</sub>	mm	max. 428
Lamp length l <sub>2</sub>	mm	max. 382
LCL a	mm	167.5
Bulb diameter d	mm	70
Average service life	h	1500
Warranty	h	1000
Base	Cathode	SFaX 27-14
	Anode	SFaX 27-13

\*) w = luminance half width value; h = height of luminance area (corresponds to electrode gap, hot)

### ■ Lamp operation

Maximum permissible base temperature	230 °C
Cooling	Forced cooling / fan
Min. air flow velocity around discharge vessel	6 m/s
Operating position	s 15 (vertical ± 15° ; anode up)

